




eye and eye						rated capacity (lbs)		
vertical	1-ply	2-ply	choker	1-ply	2-ply	basket	1-ply	2-ply
1"	1600	3200	1"	1250	2500	1"	3200	6400
2"	3200	6400	2"	2500	5000	2"	6400	12800
3"	4800	9300	3"	3800	7440	3"	9600	18600
4"	6400	11500	4"	5000	9200	4"	12800	23000



endless						rated capacity (lbs)		
vertical	1-ply	2-ply	choker	1-ply	2-ply	basket	1-ply	2-ply
1"	3200	6200	1"	2560	5000	1"	6400	12400
2"	6400	12400	2"	5000	9920	2"	12800	24800
3"	9300	18600	3"	7440	14880	3"	18600	37200
4"	12400	22000	4"	9920	17600	4"	24800	44000

While HDP™ offers superior cut and abrasion resistance, it should be noted that load edges in contact with ANY type of synthetic sling must be "protected" with materials of sufficient thickness or strength to prevent sling damage. The protection must be installed and evaluated for suitability by raising the load, slightly, and then lowering the load down for an inspection of the sling and the protection devices. Several "test" lifts may be necessary to determine the proper form of protection for a successful lift.

CORPORATE ADDRESS

Philadelphia
 1230 Old York Rd.
 Suite 101
 Warminster, PA 18974
 Tel 800 478-4651

OFFICES

Chicago
 4155 Grove Avenue
 Gurnee, IL 60031
 Tel 800 323-0852

Houston

7266 Wynnpark
 Houston, TX 77008
 Tel 800 299-0900

Seattle/Tacoma

19632 70th Ave. S.
 Unit 1
 Kent, WA 98032
 Tel 877-4LIFTEX